PREMIER

Qmax2

The ALL New Comprehensive Contamination Sorter

Highlights

- Leader of Sorting Technics
- Removes various types of White and Transparent PP including Strings
- Modern Technology with wide Visible and Invisible Spectrum together with UltraSonic Detection
- Positioned after Final Beater of all Blow Room Lines
- Controlled Lint Loss







Qmax2

Technical Data*

Contaminations Detected

- All Plastics including Coloured / Transparent / White PolyPropylene Strings, Sheets, Films etc,
- · Paper, Fabric, Feather, Jute bits etc

Line Integration

- At end of the Blow Room Line, connected after final beaters like Flexiclean, Supremoclean (LMW), Uniflex, A79R (Rieter), CVT or CLC (Trutzschler) and Fine Opener (Crosrol) or equivalent other makes
- · Material Flow from Top to Bottom
- · Input duct: 1100 x 80 mm

Key Technology

- Precise detection using Color De-coding module with Visible Spectrum and Dual Core High Speed Parallel Image processing
- InfraRed, UV and Ultrasonic Modules for effective detection of Transparent and White PP
- · Focused 'Transfer Zone' Ejection System

Power Supply

- Single Phase 1.5 kW Consumption (for machine electronics)
- Three Phase 0.75 kW Consumption (for evacuation motor)

Configuration

- · Production rate up to 1200 kg/h
- Material velocity up to 20 m/sec
- · Auto correction for tuft speed variations

Material Ejection

 Pneumatic ejection and Automatic removal of Ejected Material

Output Parameters

- · Ejections: Shift wise and Mix wise
- · Alarm for exceptions

Calibration

· Automatic and Manual Calibration

Ambient Conditions

• Relative humidity: 40 to 65%

• Temperature : 5° to 55°c

Compressed Air Requirement

- Approx 3 m³/hr at 6 Bar
- * Subject to change without prior notice

premier evolvics pvt. ltd.

SF No. 79/6, Kulathur Road Venkitapuram Post Coimbatore - 641 062, India

Phone : +91 422 6611000 Fax : +91 422 6611005 E mail : sales@premier-1.com

www.premier-1.com



