

Your air. We care.

# Rotary Pre-Filter Unit



The efficient and space-saving solution for pre-filtration in the textile and nonwoven industries



Rotary Pre-Filter Unit in TexPac

The automatic Rotary Pre-Filter Unit is ideal as a preliminary filtration stage of larger air streams, heavily charged with waste, coming from the production machines. It is a part of the proven compact centralized air handling system TexPac and optimally combinable with several function modules. This unit captivates by its simple and space-saving design and its reliable functionality.

### Features

The pre-filter part with the rotating filter disc and the stationary suction nozzle is integrated in a sturdy sheet steel housing. The access is ensured by a lockable service door with big inspection window. The cleaning is effected continuously, with a small air volume, by the suction nozzle. The coarse particles and the fibres sucked off are either conveyed to the disposal station or recycled. A pressure-controlled device protects the filter screen against overloading. By means of selectable parameters, such as mesh size of filter screen, rotation speed, etc., the pre-filter can be optimally adapted to varying operational conditions.

### Advantages

- No filter chamber to be provided by customer
- Small space requirement and simple installation
- Individually adjustable to given circumstances
- Applicable even for high negative pressures (up to approx. 3000 Pa)
- Simple monitoring and easy access for control and maintenance
- Reliable operation thanks to continuous suction

### Options

- Filter screens available in several types (mesh sizes), also in steel
- Rotation speed of filter disc adjustable during operation for varying operational requirements
- Connection box for pipings

### Technical data

Type	Size A	Size B
Width (mm)	1520	2128
Height (mm)	1520	2128
Length (mm)	912	912
Surface of filter screen (m <sup>2</sup> )	1.44	3.0
Air flow rate (m <sup>3</sup> /h)	12 000–35 000	30 000–75 000
Nominal suction air flow rate (m <sup>3</sup> /h)	1500	2200
Nominal pressure loss (Pa)	200–400	200–400
Rated output of drive motor (kW)	0.37/0.55	0.37/0.55

Zellweger Luwa AG  
 Division Luwa  
 Wilstrasse 11  
 CH-8610 Uster  
 Phone +41 (0)44 943 51 51  
 Fax +41 (0)44 943 51 52

[www.luwa.com](http://www.luwa.com)