



ALUPRESS AND EASYFIT COTS



**JKS OFFERS A WIDE RANGE OF COTS WITH HARDNESS
FROM 65°A TO 90° A
MANUFACTURED FROM THE NEWEST GENERATION OF
POLYMERS AND CHEMICALS
AVAILABLE IN ALL CONSTRUCTIONS**

JKS GG 65

SHORE HARDNESS 65° A

COLOUR: GREENISH GREY

APPLICATIONS :

FRONT ROLLER K 44

FIBRE:

100 % COTTON

ABOVE NE 40

GRINDING INTERVALS: APPROX. 30 DAYS

JKS BY 66

SHORE HARDNESS 66° A

COLOUR: GOLDEN YELLOW

APPLICATIONS:

FRONT ROLLER ELITE/K 44/RoCoS

FIBRE:

100 % COTTON

MEDIUM TO FINE COUNT

REDUCTION IN THIN AND THICK PLACES

DEPENDING ON COUNT UP TO 90 DAYS

JKS BE 68

SHORE HARDNESS 68° A

COLOUR: BLUE

APPLICATION:

FRONT ROLLER

FIBRE:

COTTON/CVC/T.C./CV

COARSE TO MEDIUM COUNT

GRINDING INTERVALS:

APPROX: 70-100 DAYS

JKS P 69

SHORE HARDNESS 69° A

COLOUR: LIGHT PINK

APPLICATIONS:

FOR COMPACT K 44/RoCoS

FIBRE:

COTTON/CVC/TC

COARSE TO MEDIUM COUNT

MID SOFT COT WITH BETTER ABRASION

ZERO TRAVERS: 15 DAYS GRINDING

CONVENTIAL SPINNING: 90 DAYS GRINDING

JKS LG 70

SHORE HARDNESS 70° A

COLOUR: LIGHT GREY

APPLICATIONS:

FRONT ROLLER

FIBRE:

COTTON/BLENDS

FINE COUNT SYNTHETIC

WOOL

JKS GR 75

SHORE HARDNESS 75° A

COLOUR: GREEN

APPLICATIONS:

FRONT ROLLER

FIBRE:

COTTON/BLENDS

COARSE TO MEDIUM COUNT

SYNTHETIC

JKS G 83

SHORE HARDNESS 83° A

COLOUR: GREY

APPLICATIONS:

FRONT AND BACK ROLLER

ALL FIBRE:

UNIVERSAL AND TROUBLE FREE COT

JKS TB 85

SHORE HARDNESS 85° A

COLOUR: BLUISH GREEN

APPLICATIONS:

FRONT AND BACK ROLLER

FIBRE

ACRYLIC

SYNTHETIC

BENEFIT:

ABRASION RESISTANT

ANTILAPPING

JKS Y 90

SHORE HARDNESS 90° A

COLOUR: YELLOW

APPLICATIONS:

BACK ROLLER

FIBRE

ACRYLIC

KEVLAR